

P23G/P23GW

Feature-rich business IP Phone

P23G/P23GW multi-functional color screen Wi-Fi phone, equipped with 2.8-inch large IPS color screen with backlight, continuation of the original stylish design, giving you a comfortable visual collaboration experience. The built-in Gigabit Ethernet ports, PoE and USB2.0 port of P23 series support access USB flash drive, EHS10 adapter, Bluetooth dongle and other device access to meet the office needs in different scenarios. Moreover, P23GW has built-in 2.4G & 5GHz dual-band Wi-Fi module to achieve high-speed data communication and provide you with the more efficient co-working services.

















Key Features and Benefits



HD voice, Quality calls

P23 series supports Opus wideband codec with advanced echo cancellation technology and intelligent noise cancellation technology to provide users with HD voice for better quality voice calls.



Dual-band Wi-Fi and Convenient networking

Flyingvoice P23 series support 2.4G & 5G Hz WiFi and PoE module to meet the office needs of enterprise wired/wireless network access.



USB expansion, Rich Application scenarios

P23 series integrates USB2.0 interface, supports EHS10 adapter, Bluetooth and 5G Wi-Fi dongle, realizes USB flash recording, DECT and Bluetooth wireless headset to access calls, providing users with more wireless office services.



Simple installation and Easy Deployment

Flyingvoice P23 series can be easily deployed and managed by online platforms such as FACS and FRPS and auto-provisioning modes FTP/TFTP/HTTP/HTTPS/TR069, greatly saving on operation and maintenance time.

- 2.8" 320×240px backlight LCD screen
- 8 SIP accounts
- Built-in 2.4G & 5G Hz Wi-Fi (P23GW)
- Opus codec support
- Dual Gigabit Ethernet ports
- USB 2.0 port for USB recording
- Support PoE
- Dect headset. RJ9 headset
- 6-Way conferencing
- Stand with 2 adjustable angles
- Wall mountable



P23G/P23GW Specifications

Phone Features		
LCD Screen	> 2.8" 320 x 240px color screen with backlight > 16-bit depth color	
Function Keys	> 12 Function Keys: M1, M2, M3, M4, M5, M6, mute, headset, transfer, redial, hands-free speakerphone > 8 Line keys, 4 Soft Keys, 5 Navigate Keys, Volume+/-	
SIP Accounts	> 8 SIP accounts	
Wi-Fi	> 2.4GHz & 5GHz Wi-Fi (P23G: 2.4G Hz Wi-Fi)	
USB Port	> USB call recording through USB flash drive > Wireless Headset Adapter EHS10 > Bluetooth earphone through BT50	
Ethernet Port	> 2*10/100/1000M (adaptive) > Support PoE	
Other Ports	> 1 x Handset port, > 1 x RJ9 Headset port - Wire-controlled RJ9 headset through HP200	
Call Features		
Basic function	> Call hold, Mute, DND, Redial, Auto answer, One-touch speed dial, Hotline, SMS, Call forward, Call waiting, Call transfer (attended/blind), Paging, Voice mail, BLF, Anonymous call, Anonymous call rejection, Message waiting indicator (MWI), Hot desking	
Direct IP Call	> Supported	
Phone book	> 2000 records; Phonebook search/import/export; XML/LDAP remote phonebook; Black list	
Call history	> 60 records; Call history: all/missed/dialed/received	
Conference Call	> 6-way conference, Network conference	
Audio Features		
HD Voice	> HD handset, HD speaker	
Audio Codec	> G.722, Opus, AMR-WB(Optional), G.711WB(Optional), G.711(A/u), iLBC, G.729A/B, G.723, G.726, AMR-NB(Optional)	
DTMF	> In-band, RFC 2833, SIP info	
Other Features	> AEC, VAD, CNG, PLC, AGC, AJB	
Network		
Network Safety	 SIP Related Features: SIP v1 (RFC2543), v2 (RFC3261), NAT Traversal by STUN SIP link mode: Proxy mode and peer-to-peer SIP link mode Call server redundancy supported Network Features: Static IP and DHCP, IPv4 /IPv6, Dual stack IPv4/IPv6, ARP/RARP, DNS A/DNS SRV/DNS NAPTR LLDP/CDP/DHCP VLAN; IEEE802.1X; OpenVPN; DSCP, 802.1p QoS, SSL Time and Date synchronization: SNTP, PBX, DHCP Transport Feature: UDP/TCP/TLS; RTP/RTCP/SRTP 	

Configuration & Maintenance		
Auto-provision	> TR069 (TR104/TR106) > FTP/TFTP/HTTPS for Auto Provisioning > Cloud device management: FACS > Cloud device management: FRPS > DHCP Option66	
Configuration	> Supports web configuration > Factory reset, reboot > Packet capture, system log	
Others		
Physical Features	> New Stand, Wall mountable > AC/DC Adapter, AC Input: 100~240V, 50~60Hz > DC Output: 5V, 1A;5V,2A (Only P23GW) > Power consumption (PSU): 1.6~3.0W > Power consumption (PoE): 1.7W~3.3W > Relative humidity: 10%~90% (No Condensing) - Storage temperature: -20~ 70°C - Operation temperature: 0~45°C > Dimension (W x D x H): 190mm × 188.5mm × 41mm	
Package Content		
Details	Packing List: > Flyingvoice P23G/P23GW IP Phone, Power adapter (optional) > Handset with handset cord, Ethernet cable, Stand > Quick Start Guide Size: > Qty/CTN: 10 PCS, N.W/CTN: 8.31 kg, G.W/CTN: 10.66 kg > Giftbox size: 270mm × 195mm × 78mm > Carton size: 440mm × 410mm × 290mm	
Certification & Compatibility		
Certificated by	CEF© róhs	
Compatible with	♥ broadsoft metaswitch **Yeastar	



About Flyingvoice

Flyingvoice is a leading manufacturer of VoIP phones, VoIP adapters and VoIP routers, which are widely used throughout the world and highly praised by international carriers, ITSP, ISP and company users.

Driven by ongoing innovation of VoWLAN, Flyingvoice is committed to making easier VoIP products by enabling the enterprise network and united communication. Our people are continuously improving our products and expanding product applications tailored to clients' requirements, which make you collaborate securely, effectively and efficiently – anytime & anywhere.

Copyright

Copyright © Flyingvoice Network Technology Co., Ltd. All rights reserved. No parts of this publication may be reproduced or transmit- ted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Flyingvoice Network Technology Co., Ltd.

Technical Support

Visit www.flyingvoice.com for product documents and FAQ, or contact Flyingvoice by email at support@flyingvoice.com. We'll get you the help you need.



Flyingvoice Network Technology Co., Ltd.Website:

www.flyingvoice.com

Add: 1801-1802, Building 1, Chongwen Park, Nanshan Zhiyuan,

Nanshan District, Shenzhen, China

Copyright© Flyingvoice Network Technology Co., Ltd. All Rights Reserved